



- 備註：
1. 材質：SPCC t=3mm
 2. 表面處理：烤黑纖維漆
 3. 顏色：黑色
 4. 色差： $\Delta E \leq 1.5$ ($-1 \leq \Delta L \leq 1$ ； $-0.8 \leq \Delta a \leq 0.8$ ； $-0.8 \leq \Delta b \leq 0.8$)，色差值須符合規範且與承認樣品目視不得有明顯色差。
 5. 不可有毛邊 或 毛邊 $\leq 0.05\text{mm}$ 且不可割手
 6. 毛邊方向如圖標示: 兩面皆不可有毛邊
 7. 滾壓方向(紋路方向)如圖標示
 8. 變形量如圖標示
 9. 腳接boss強度須能承受側向正推力10kg力以上
 10. 未標示之R為0.1R
 11. 未指定之公差,請參照公差表 A class
 12. 外觀檢驗標準：成品表面不可有油脂、銹蝕或影響功能的傷痕
 13. 本品需符合AVer Info. IQ-S-RD012規範之規定,如果是GP(Sony)用料需符合之規定如下:
 - (1) 「禁止使用 SS-00259 中1級環境管理物質」。
 - (2) 「使用 SONY 指定原材料「再生樹脂、被覆線材(電磁線與漆包線除外)」時，必須從 SONY (GP Supplier List) 選定」。
 14. The component has to meet the following requirements as specified in AVer Info. internal document IQ-S-RD012. If the GP(Sony) component has to meet the following requirements:
 - (1) Should not contain any environment-related substance categorized as Level 1 in SONY's SS-00259.
 - (2) All of the designated raw materials, Recycled Resin and Coated Wire (excluding Magnetic wire and Enameled wire), must be purchased from the suppliers as identified on SONY's GP Supplier List.
 15. 標示○為重點尺寸
 16. 重點尺寸：1, 2, 3 需做 CpK
 17. 不易量測之重點尺寸以治具檢驗，治具相關資料需列入承認書內容

機密 (Confidentiality)

					註：1. 金手指PCB類,未標示之尺寸公差為±0.12mm,其它PCB類及其它機構件未標註之公差如公差表。	
註冊 MARK NO.	2021/08/01	Original	your name		NOTE：1. For PCB with golden finger, unspecified tolerance is ±0.12mm, other kinds of PCB and mechanical parts, unspecified tolerance see tolerance table.	
	日期 DATE	內部 DESCRIPTION	簽 SIGNATURE			

公差表			Unspecified tolerance			單位 UNIT	材質 MAT.	SPCC t=3mm	料號 PART NO.	112AS933-BF3	品名 MODEL NAME	SHEET_X_S933_WALL MOUNT
LENGTH			TOLERANCE									
			A class	B class	C class	比例 SCALE	1:1	版本 VERSION	日期 DATE	2024/03/01	圖號 DRAW NO.	S933_W_M_1
			0~6mm	±0.10mm	±0.05mm							
			7~30mm	±0.15mm	±0.10mm	圖號 DRAW NO.	S933_W_M_1					
			31~100mm	±0.20mm	±0.15mm							
			101~180mm	±0.25mm	±0.20mm	圖號 DRAW NO.	S933_W_M_1					
			181~300mm	±0.30mm	±0.25mm							
			301~600mm	±0.50mm	±0.30mm	圖號 DRAW NO.	S933_W_M_1					
			Plastic Parts Angle	±0.5°								
			Metal Parts Angle	±1°								

